



# Power Incentive

## ■ MENU

## ● Rigid SMD LED Strip (TOP SMD LED TYPE)

## ■ Indhold/Contents

### ■ Kontakt/Contact

### ■ Farve koordinater /Colour Coordinates

### Application

Number	Color	Length (m)	LED Q'ty	LED Type	Light Output (mcd)	Light Output (lumen)	Beam Angle (degrees)	Voltage (V DC)	Current (Amps)	Max. Power Consumption (W)	Continuous Connection (m)
SC-SS-R	Red	0.5	30	Top SMD LED 3528 (2012)	30x600	45	120	12	0.34-0.4	4.8	15
SC-SS-Y	Yellow	0.5	30		30x600	45	120	12	0.34-0.4	4.8	15
SC-SS-B	Blue	0.5	30		30x250	30	120	12	0.34-0.4	4.8	15
SC-SS-G	Green	0.5	30		30x650	50	120	12	0.34-0.4	4.8	15
SC-SS-W	White	0.5	30		30x1200	60	120	12	0.34-0.4	4.8	15
SC-SS-WW	Warm White	0.5	30		30x850	45	120	12	0.34-0.4	4.8	15
SC-SS-RGB	RGB	0.6	30	Top SMD LED 5060	30x1500	135	120	12	0.51-0.6	7.2	15
SC-JSS-R	Red	0.5	30	Top SMD LED 3528(2012)	30x600	45	120	12	0.34-0.4	4.8	15
SC-JSS-Y	Yellow	0.5	30		30x600	45	120	12	0.34-0.4	4.8	15
SC-JSS-B	Blue	0.5	30		30x250	30	120	12	0.34-0.4	4.8	15
SC-JSS-G	Green	0.5	30		30x650	50	120	12	0.34-0.4	4.8	15
SC-JSS-W	White	0.5	30		30x1200	60	120	12	0.34-0.4	4.8	15
SC-JSS-WW	Warm White	0.5	30		30x850	45	120	12	0.34-0.4	4.8	15
SC-JSS-RGB	RGB	0.6	30	Top SMD LED 5060	30x1500	135	120	12	0.51-0.6	7.2	15

1. Cove lighting
2. Architectural lights for canopy, corridor, window, archway
3. Backlight or edge lighting for signs
4. DIY lights for home use
5. Decorative lights for holiday, event, show, exhibition
6. Decorative lights for automobile
7. Ideal replacement of incandescent and fluorescent light

## Features

1. Can be cut every 3 LEDs along the mark on PCB
2. Mounting accessories available in 3M tape and bracket
3. Low power consumption; no heat
4. Compact size to suit narrow space installation
5. SC-JSS can be connected without light break thanks to the jack connector
6. Well-protected package for shipment

